

CURLMOPT_PIPELINING_SITE_BL(3) curl_multi_setopt options CURLMOPT_PIPELINING_SITE_BL(3)

NAME

CURLMOPT_PIPELINING_SITE_BL – pipelining host blacklist

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLMcode curl_multi_setopt(CURLM *handle, CURLMOPT_PIPELINING_SITE_BL, char **hosts);
```

DESCRIPTION

Pass a **hosts** array of char *, ending with a NULL entry. This is a list of sites that are blacklisted from pipelining, i.e sites that are known to not support HTTP pipelining. The array is copied by libcurl.

Pass a NULL pointer to clear the blacklist.

DEFAULT

The default value is NULL, which means that there is no blacklist.

PROTOCOLS

HTTP(S)

EXAMPLE

```
site_blacklist[] =
{
    "www.haxx.se",
    "www.example.com:1234",
    NULL
};
```

```
curl_multi_setopt(m, CURLMOPT_PIPELINING_SITE_BL, site_blacklist);
```

AVAILABILITY

Added in 7.30.0

RETURN VALUE

Returns CURLM_OK if the option is supported, and CURLM_UNKNOWN_OPTION if not.

SEE ALSO

CURLMOPT_PIPELINING(3), CURLMOPT_PIPELINING_SERVER_BL(3),